

JMJ 型接中间轴型弹性膜片联轴器
基本参数和主要尺寸 (JB/T 9147-1999)

型号	公称 转矩 N•m	瞬时最大 转矩 N•m	最大 转速 rpm	轴孔直径 d1、d2	轴孔长度 mm			D mm	C mm	A mm	重量 kg		转动惯 量 kg•m ²
					J1 型	Y 型	L (推 荐)				S	每 增加 1m	
					L	L							
JMJ1	63	100	9300	20, 22, 24	38	52	40	92	70	8+0.2	2	4.1	0.002
				25, 28	44	62							
				30, 32, 35, 38	60	82							
JMJ2	100	200	8400	25, 28	44	62	45	102	80		2.9		0.003
				30, 32, 35, 38	60	82							
				40, 42, 45	84	112							
JMJ3	250	400	6700	30, 32, 35, 38	60	82	55	128	96		5.7		0.009
				40, 42, 45, 48, 50, 55	84	112							
JMJ4	500	800	5900	35, 38	60	82	65	145	116	11+0.3	8.5	8	0.017
				40, 42, 45, 48, 50, 55	84	112							
				60, 63, 65	107	142							
JMJ5	800	1250	5100	40, 42, 45, 48, 50, 55	84	112	75	168	136	14+0.3	12.5		0.034
				60, 63, 65, 70, 71, 75	107	142							
JMJ6	1250	2000	4750	45, 48, 50, 55, 56	84	112		180		15+0.4	16.5	12	0.053
				60, 63, 65, 70, 71, 75	107	142							
				80	132	172							
JMJ7	2000	3150	4300	50, 55, 56	84	112	80	200	140		21	19	0.082
				60, 63, 65, 70, 71, 75	107	142							
				80, 85	132	172							
JMJ8	2500	4000	4200	55, 56	82	112		205		20+0.4	23		0.092
				60, 63, 65, 70, 71, 75	107	142							
				80, 85	132	172							
JMJ9	3150	5000	4000	55, 56	84	112	90	215	160		27	21	0.117
				60, 63, 65, 70, 71, 75	107	142							
				80, 85, 90	132	172							
JMJ10	4000	6300	3650	60, 63, 65, 70, 71, 75	107	142	100	235	170		36		0.191
				80, 85, 90, 95	132	172							
JMJ11	5000	8000	3400	60, 63, 65, 70, 71, 75	107	142	100	250	170	23+0.5	42	26	0.252
				80, 85, 90, 95	132	172							
				100	167	212							
JMJ12	6300	10000	3200	60, 63, 65, 70, 71, 75	107	142	110	270	190		50		0.349
				80, 85, 90, 95	132	172							
				100, 110	167	212							
JMJ13	8000	12500	2850	65, 70, 71, 75	107	142	115	300	200	27+0.6	66	47	0.56
				80, 85, 90, 95	132	172							
				100, 110	167	212							
JMJ14	10000	16000	2700	70, 71, 75	107	142	125	320	220	27+0.6	78		0.75
				80, 85, 90, 95	132	172							
				100, 110, 120, 125	167	212							
JMJ15	12500	20000	2450	75	107	142	140	350	240	32+0.7	110	51	1.26
				80, 85, 90, 95	132	172							
				100, 110, 120, 125	167	212							
				130	202	252							

JMJ 型接中间轴型弹性膜片联轴器
基本参数和主要尺寸 (JB/T 9147-1999)

型号	公称转矩 N•m	瞬时最大转矩 N•m	最大转速 rpm	轴孔直径 d1、d2	轴孔长度 mm			D mm	C mm	A mm	重量 kg		转动惯量 kg • m ²
					J1 型	Y 型	L (推荐)				S	每增加 1m	
					L	L							
JM16	16000	25000	2300	80, 85, 90, 95	132	172	145	370	250	32±0.7	125	72	1.63
				100, 110, 120, 125	167	212							
				130, 140	202	252							
JM17	20000	31500	2150	90, 95	132	172	165	400	290		160		2.45
				100, 110, 120, 125	167	212							
				130, 140, 150	202	252							
				160	242	302							
JM18	25000	40000	1950	100, 110, 120, 125	167	212	175	440	300	220	3.99		
				130, 140, 150	202	252							
				160, 170	242	302							
JM19	31500	50000	1850	100, 110, 120, 125	167	212	185	460	320	38±0.9	245	89	4.98
				130, 140, 150	202	252							
				160, 170, 180	242	302							
JM20	35500	56000	1800	120, 125	167	212	200	480	350		275		6.28
				130, 140, 150	202	252							
				160.170, 180	242	302							
				190, 200	282	352							
JM21	40000	63000	1700	120, 125	167	212	210	500	370	38±0.5	320	89	7.68
				130, 140, 150	202	252							
				160, 170, 180	242	302							
				190, 200	282	352							
JM22	50000	80000	1600	140, 150	202	252	220	540	380	44±1	400	110	11.6
				160, 170, 180	242	302							
				190, 200, 220	282	352							
JM23	63000	100000	1450	140, 150	202	252	240	600	410	50±1.2	560	145	19.8
				160, 170, 180	242	302							
				190, 200, 220	282	352							
				240	330	410							
JM24	80000	125000	1400	160, 170, 180	242	302	255	620	440		620		23.6
				190, 200, 220	282	352							
				240, 250	330	410							
JM25	90000	140000	1300	180	242	302	275	660	480	740	31.9		
				190, 200, 220	282	352							
				240, 250, 260	330	410							
				280	380	470							
JM26	112000	180000	1200	180	242	302	295	720	510	60±1.4	970	190	50.4
				190, 200, 220	282	352							
				240, 250, 260	330	410							
				280, 300	380	470							
JM27	140000	200000	1150	220	282	352	300	740	520		1050		57
				240, 250, 260	330	410							
				280, 300	380	470							

JMJ 型接中间轴型弹性膜片联轴器
基本参数和主要尺寸 (JB/T 9147-1999)

型	公称 转 矩 kN·m	瞬时 最 大 转矩 kN·m	最大 转 速 rpm	轴孔 直径 d1>d2	轴孔长度 mm			D mm	C mm	A mm	重量 kg		转动 惯量 kg·m ²				
					J1 型	Y 型	L 推 荐				S	每增 加 1m					
					L	L											
JM28	160	224	1100	240, 250, 260	330	410	320	770	560	60±1.4	1200	215	69.4				
				280, 300	380	470					1400		95.5				
JM29	180	280	1050	250, 260	330	410	350	820	600					60±1.4	1400	215	95.5
				280, 300, 320	380	470											
				340	450	550											
JM30	280	450	1000	280, 300, 320	380	470	350	875	620		50±1.6		1400	235	96.5		
				340, 360	450	550				109.5							
JM31	400	630	930	300, 320	380	470	350	935	630	66+1	1800	290	142				
				340, 360, 380	450	550							152				
				400	540	650							162				
JM32	450	710	880	320	380	470	380	1030	690		66+1	2250	330	194			
				340, 360, 380	450	550								224			
				400, 420	540	650								240			
JM33	560	900	820	360, 380	540	650	400	1080	726	66+2.2		2750	390	271			
				400, 420, 440,			460	1160	836	70±2.3		3500	450	325			
JM34	1000	1600	740	400, 420, 440,										387			
				460, 480,			520	1290	946	82±2.6	5000	570	570				
				JM35										1400	2240	680	440, 450, 460,
JM36	2000	3150	620	480, 500			540	650	570	1410	1040	92±2.8	6600	710	1050		
				530, 560, 600	680	800	1290										
JM37	2800	4000	570	450, 460,	540	640	610	1530	1100	105 + 3	8400	880	1630				
				530, 560,	680	800							1950				
JM38	4000	6000	520	560, 600, 630	670	1670	1210	11+3.7	11000	1050	2670						
				670, 710							780	—	3030				
JM39	5000	8000	480	600, 630	680	800	730	1830	1320	12 + 3.7	14500	1350	4060				
				670, 710, 750	780	—							4800				
JM40	6300	10000	430	670, 710, 750	780	800	2000	1450	130±4	19000	1600	6600					
				800, 850	880							7500					
JM41	8000	12500	400	750	780							2200	1600	14+4.4	25000	1850	10400
				800, 850	960				2400	1760	32000						2100
JM42	10000	16000	350	800, 850								880	15200				
				900, 950	980				17400								