

JSP 型带制动盘蛇形弹簧联轴器
基本参数和主要尺寸 (JB/T 8869-2000)

型号	公称转矩 T _n N•m	许用转速 [n] rpm	制动盘		轴孔直径 d	L	L1	D	D1	间隙 t	质量 m (无孔无盘) kg	润滑油 kg
			直径 D0	宽度 B								
JSP1	200	3800	315	30	20, 22, 24	63	88	150	125	3	9.579	0.086
					25, 28							
					30, 32, 35, 38							
					40, 42, 45, 48, 50							
JSP2	315	3200			25, 28	76		162	133		12.349	0.1135
					30, 32, 35, 38							
					40, 42, 45, 48, 50, 55,							
					60, 63							
JSP3	630	2800			30, 32, 35, 38	88		193	152		19.794	0.1725
					40, 42, 45, 48, 50, 55,							
					60, 63, 65, 70, 71, 75							
JSP4	1000	2700			35, 38	98		212	179		28.42	0.254
					40, 42, 45, 48, 50, 55,							
					60, 63, 65, 70, 71, 75							
					80, 85							
JSP5	1800	2400			40, 42, 45, 48, 50, 55,	120		119	250		216	47.76
			60, 63, 65, 70, 71, 75									
			80, 85, 90, 95									
			100									
JSP6	2800	2200	450	127	146	270	241	64.922	0.5085			
			50, 55, 56									
			60, 63, 65, 70, 71, 75									
			80, 85, 90, 95									
JSP7	4500	2000	500	100, 110	150	149	308	276	91.35	0.729		
				60, 63, 65, 70, 71, 75								
				80, 85, 90, 95								
JSP8	6300	1800	560	130, 140, 150	162	152	346	295	131.65	0.908		
				70, 71, 75								
				80, 85, 90, 95								

JSP 型带制动盘蛇形弹簧联轴器

基本参数和主要尺寸（JB/T 8869-2000）/mm

型号	公称转矩 T _n N•m	许用转速 [n] rpm	制动盘		轴孔直径 d	L	L1	D	D1	间隙 t	质量 m(无孔 无盘) kg	润滑油 kg
			直径 D0	宽度 B								
JSP9	9000	1600	630	30	80, 85, 90, 95	184	158	384	330	6	184.798	1.135
					100, 110, 120, 125							
					130, 140, 150							
					160, 170, 180							
JSP10	12500	1500	800		90, 95	182	183	453	368	6	253.332	1.9068
					100, 110, 120, 125							
					130, 140, 150							
					160, 170, 180							
					190, 200							
JSP11	16000	1300	900		100, 110, 120, 125	198	198	500	400	6	336.414	2.815
					130, 140, 150							
					160, 170, 180							
					190, 200, 220							

◆注：1.若轴孔型式按 GB/T 3852 与制造厂协商。2.质量是无孔无盘的计算近似值。

JSP 型带制动盘型蛇形弹簧联轴器（JB/T 8869-2000）

