


Z12A 型胀套 Z12A type locking assemblies



基本尺寸和参数 Basic dimensions and parameters of the locking assemblies, type Z12A

规格 sizes d × D	基本尺寸					内六角螺钉			额定负荷		Pf	Pf'	G(kg)
	Basic dimensions					In hex agons screws			Rated load		N/mm ²	N/mm ²	
	d	D	I	L	L1	规格 ch sizes	数量 n QTY	MA N.m	Ft KN	Mt KN.m			
	mm												
25×55	25	55	32	40	46	M6	6	17	67	0.84	297	101	0.47
28×55	28	55	32	40	46	M6	6	17	67	0.94	265	101	0.44
30×55	30	55	32	40	46	M6	6	17	67	1.0	248	101	0.42
35×60	35	60	44	54	60	M6	7	17	74	1.3	165	87	1.0
40×65	40	65	44	54	62	M8	7	41	145	2.9	282	116	1.1
45×75	45	75	44	54	62	M8	7	41	145	3.26	251	116	1.2
50×80	50	80	56	64	72	M8	8	41	165	4.15	200	98	1.4
55×85	55	85	56	64	72	M8	9	41	186	5.15	205	104	1.6
60×90	60	90	56	64	72	M8	10	41	207	6.2	202	106	1.7
65×95	65	95	56	64	72	M8	10	41	207	6.75	187	100	1.9
70×110	70	110	70	78	88	M10	10	83	329	11.5	223	114	3.1
80×120	80	120	70	78	88	M10	11	83	362	14.5	215	115	3.5
90×130	90	130	70	78	88	M10	12	83	390	17.8	208	115	3.8
100×145	100	145	90	100	112	M12	14	145	527	26.3	200	107	6.1
110×155	110	155	90	100	112	M12	17	145	575	31.8	198	110	6.6
120×165	120	165	90	100	112	M12	18	145	670	40.4	212	120	7.2
130×180	130	180	104	116	130	M14	16	230	759	49	180	112	11.1
140×190	140	190	104	116	130	M14	18	230	842.8	59	186	124	11.8
150×200	150	200	104	116	130	M14	19	230	896.6	67	185	127	12.6
160×210	160	210	104	116	130	M14	20	230	950	76	183	128	13.4
170×225	170	225	134	146	162	M16	19	355	1223.5	104	172	113	19.6
180×235	180	235	134	146	162	M16	20	355	1288.8	116	172	115	20.6
190×250	190	250	134	146	162	M16	21	355	1363	129.5	172	116	23.8
200×260	200	260	134	146	162	M16	22	355	1437.5	143.7	172	112	24.9
220×285	220	285	134	146	162	M16	24	355	1581.8	174	172	115	29.6
240×305	240	305	134	146	162	M16	26	355	1725	207	172	119	31.9
260×325	260	325	134	146	162	M16	28	355	1846	240	170	117	34.3
280×335	280	355	165	177	197	M20	24	690	2428.5	340	168	117	52
300×375	300	375	165	177	197	M20	25	690	2540	381	161	123	55.3
320×405	320	405	165	177	197	M20	28	690	2881	461	175	119	67.3
340×425	340	425	165	177	197	M20	29	690	2994	509	171	119	71
360×455	360	455	190	202	224	M22	28	930	3588.8	646	169	115	96.5
380×475	380	475	190	202	224	M22	30	930	3821	726	170	115	101.2
400×495	400	495	190	202	224	M22	31	930	3960	792	168	120	106
420×515	420	515	190	202	224	M22	32	930	4100	861	165	116	110.7
440×535	440	535	190	202	224	M22	24	930	4260	937	165	112	110
460×555	460	555	190	202	224	M22	24	930	4260	980	158	107	113
480×575	480	575	190	202	224	M22	28	930	5000	1200	176	121	118
500×595	500	595	190	202	224	M22	28	930	5000	1240	169	117	122
520×615	520	615	190	202	224	M22	30	930	5330	1390	174	121	126
540×635	540	635	190	202	224	M22	30	930	5330	1440	168	117	131
560×655	560	655	190	202	224	M22	32	930	5680	1590	172	121	135
580×675	580	675	190	202	224	M22	33	930	5860	1705	172	121	140
600×695	600	695	190	202	224	M22	33	930	5860	1760	166	118	144

注：Z12A 型胀紧联结套螺钉的机械性能等级为 12.9 级。