


Z19A 型胀套 Z19A type locking assemblies



基本尺寸和参数 Basic dimensions and parameters of the locking assemblies, type Z19A

规格 sizes×D	基本尺寸 Basicdimensions					圆螺母 Roundaut		额定负荷 Ratedload		Pf N/mm ²	Pf N/mm ²	G(kg)
	d	D	E	H	B	规格 chsizes	MA N.m	MtN.m	FtKN			
	mm											
14×25	14	25	32	16.5	6.5	M20×1	95	38	5.10	200	110	0.05
15×25	15	25	32	16.5	6.5	M20×1	95	41	5.50	185	110	0.04
16×25	16	25	32	16.5	6.5	M20×1	95	432	5.45	174	110	0.04
17×26	17	26	32	16.5	6.5	M20×1	95	47	5.50	164	107	0.04
18×26	18	26	32	16.5	6.5	M22×1	95	49	5.40	155	107	0.04
18×30	18	30	38	16.5	6.5	M25×1.5	160	58	6.60	185	112	0.06
19×30	19	30	38	18	6.5	M25×1.5	160	62	6.60	176	112	0.06
20×30	20	30	38	18	6.5	M25×1.5	160	66	6.60	167	111	0.06
22×32	22	32	38	18	6.5	M25×1.5	160	73	6.60	152	105	0.06
24×35	24	35	45	18	6.5	M30×1.5	220	105	8.75	185	127	0.08
25×35	25	35	45	18	6.5	M30×1.5	220	110	8.80	178	127	0.07
28×36	28	36	45	18	6.5	M32×1.5	220	120	8.55	159	124	0.06
28×40	28	40	52	18	6.5	M35×1.5	340	149	10.60	188	141	0.09
30×40	30	40	52	19.5	7	M35×1.5	340	160	10.60	164	123	0.09
32×42	32	42	52	19.5	7	M36×1.5	340	170	10.60	154	117	0.09
35×45	35	45	58	21.5	8	M40×1.5	480	230	13.10	153	120	0.11
36×45	36	45	58	21.5	8	M40×1.5	480	240	13.30	149	120	0.1
38×48	38	48	58	21.5	8	M42×1.5	480	250	13.10	141	112	0.12
38×50	38	50	58	21.5	8	M42×1.5	480	250	13.10	141	112	0.14
40×50	40	50	65	24.5	10	M42×1.5	680	310	15.50	124	93	0.14
40×52	40	52	65	24.5	10	M45×1.5	680	310	15.50	120	93	0.16
42×55	42	55	65	25.5	10	M48×1.5	680	320	15.20	114	87	0.2
45×55	45	55	70	25.5	10	M50×1.5	870	400	17.70	122	96	0.16
45×57	45	57	70	25.5	10	M50×1.5	870	400	17.70	122	96	0.2
48×60	48	60	75	25.5	10	M55×2	970	500	20.80	135	105	0.21
50×60	50	60	75	25.5	10	M55×2	970	520	20.80	130	105	0.18
50×62	50	62	75	25.5	10	M55×2	970	520	20.80	130	105	0.22
55×65	55	65	80	27.5	12	M60×2	1100	610	22.00	103	84	0.21
55×68	55	68	80	27.5	12	M60×2	1100	610	22.00	103	84	0.28
56×68	56	68	80	27.5	12	M60×2	1100	620	22.00	101	82	0.26
60×70	60	70	85	30	12	M65×2	1300	800	26.60	113	93	0.24
60×73	60	73	85	30.5	12	M65×2	1300	800	26.60	113	93	0.33
63×79	63	79	92	30.5	14	M70×2	1600	980	31.10	107	86	0.43
65×79	65	79	92	30.5	14	M70×2	1600	1010	31.00	104	86	0.38
70×84	70	84	98	31.5	14	M75×2	2000	1240	35.40	110	92	0.42

注：Z19A 型胀紧联结套螺钉的机械性能等级为 12.9 级。